



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7:

H04L 29/12, 12/46

(11) International Publication Number:

WO 00/27094

A1

(43) International Publication Date:

11 May 2000 (11.05.00)

(21) International Application Number:

PCT/CA99/01014

(22) International Filing Date:

29 October 1999 (29.10.99)

(30) Priority Data:

2,252,207

30 October 1998 (30.10.98)

CA

(71) Applicant (for all designated States except US): EICON TECHNOLOGY CORPORATION [CA/CA]; 9800 Cavendish Boulevard, Montreal, Québec H4M 2V9 (CA).

(72) Inventor; and

(75) Inventor/Applicant (for US only): MOINEAU, Gilbert [CA/CA]; 3255, Dalbé-Viau, Lachine, Québec H8T 3N3 (CA).

(74) Agents: ANGLEHART, James et al.; Swabey Ogilvy Renault, Suite 1600, 1981 McGill College Avenue, Montréal, Québec H3A 2Y3 (CA).


(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR. BY. CA. CH. CN. CR. CU. CZ. DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: DIGITAL NETWORK MODEM WITH AN INTEGRATED DHCP SERVER



(57) Abstract

The digital network modem has a built-in Dynamic Host Configuration Protocol (DHCP) mechanism for dynamically assigning network addresses to clients on the local network. To prevent confusion with a potentially existing DHCP server on the local network, an autosense mechanism is provided to detect the existence of a DHCP server and disable the internal, built-in DHCP mechanism. At power-on, the modem has no knowledge of clients on the local network, and the addresses in use are checked prior to operation. Addresses in use are placed in a list in a store of unknown addresses, and are not assigned to clients requesting DHCP addresses. When a DHCP client requests an address and has as its current address one of the addresses on the list, the current address is removed from the list. The list of unusable addresses is thus minimized and the same address will not be used for two clients.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain .	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
ΑZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IТ	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
СН	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

20

25

30

DIGITAL NETWORK MODEM WITH AN INTEGRATED DHCP SERVER

Field of the Invention

The present invention relates to a digital network modem, such as an ISDN or a DSL modem, and more particularly to a digital network modem having a dynamic host configuration protocol (DHCP) server function integrated into the modem.

Background of the Invention

To facilitate network management in local area networks (LANs), it is known to provide servers called dynamic host configuration protocol or DHCP servers. These servers respond to requests from clients connected to the network to receive assigned dynamic addresses for communication purposes on the network. The advantage of using such a dynamic address assignment is that new clients can be added easily, and the effort to manage the addresses used on the network is reduced. In most cases, a DHCP server is provided by software added to a network server.

When a network which was previously not connected to other networks or when a network needs a faster or additional connection to other networks, digital network modems are added to provide the desired connection. Network modems, such as ISDN modems, are assigned an address on the LAN. When DHCP is used, clients on the LAN are assigned their addresses and can recognize the modem as a router or gateway by consulting the DHCP, and in this way, each client does not need to have prior knowledge of any fixed address for the modem.

Computer networks are being installed in more and more residential, office and industrial environments, and the increase in the number of such networks has increased the need for skilled technicians required to configure and maintain

10

15

such networks. While computer networks were very uncommon a few years ago for home users, it is now economically feasible and desirable to interconnect computer devices in a home environment. Any simplification of the task of network management is important from the perspective of both increased reliability and reduced training for the network manager. DHCP therefore offers many practical advantages in managing a network, even for relatively small networks found in homes or small and medium businesses. While some network administrators have taken the time to obtain and install DHCP, many others have not, particularly in home and small business environments.

While it would be advantageous to provide a DHCP server function integrated with a component to be added to a network, such as a digital network modem, for those who would benefit from a DHCP, it is imperative to avoid installing two DHCP servers on the same network, since the result would be confusion and malfunction. Furthermore, having to choose between one modem including DHCP functionality and another modem without DHCP requires the manufacture, distribution and stocking of separate types of modems, and complicates the purchasing choice.

20

25

Summary of the Invention

It is therefore an object of the invention to provide in a digital network modem (i.e. a router or gateway device) a mechanism for dynamically assigning network addresses on a LAN, such as DHCP, which mechanism has an autosense feature to automatically shut itself off when the modem detects that a similar device is present on the LAN.

According to the invention, there is provided a network modem device comprising an integrated mechanism for dynamically assigning network

10

15

20

addresses on a network. The device further comprises a controller circuit connected to the integrated dynamic network address assignment mechanism and detecting the presence of a dynamic address assignment server on the network. The integrated mechanism is disabled when the dynamic address assignment server on the network is detected.

The invention also provides a method of enabling/disabling a mechanism for dynamically assigning network addresses on a network, the mechanism being integrated into a network modem device. The method comprises detecting a presence of a dynamic address assignment server on the network, and disabling the integrated mechanism when the dynamic address assignment server is detected on the network.

It is yet another object of the invention to provide a mechanism for dynamically assigning network addresses on a LAN, such as DHCP, which is able to handle a reinitialization, for example as a result of being turned off and on, without disrupting any clients on the network. According to this feature, the mechanism for dynamically assigning network addresses pings all addresses within its range at power on. The mechanism then reserves any addresses which have responded. New clients requesting dynamic addresses are assigned new addresses within the range, and existing clients request a new addresse periodically. When an existing client having one of the reserved addresses requests a new dynamic address, the address is removed from the list of unkown and reserved addresses.

Brief Description of the Drawings

The invention will be better understood by way of the following detailed description of a preferred embodiment with reference to the appended drawings, in which:

Fig. 1 is a schematic block diagram of the LAN ISDN modem according to the preferred embodiment connected to a LAN to which a configuration station and a network DHCP server are also connected.

Detailed Description of the Preferred Embodiment

As illustrated in Fig. 1, the digital modem 10 according to the preferred embodiment is an ISDN modem having a plurality of functional components shown in Fig. 1. The separation of components illustrated in the separate blocks in Fig. 1 is for the purposes of illustration only, and does not necessarily reflect the physical separation of components in the real device which is built from both hardware and software/firmware components.

When the modem 10 is connected to the Ethernet local area network (LAN) 22 and powered up, a LAN interface 12 and a modem address initializer unit 14 become active. In operation, the modem 10 directs data traffic via router 18 onto the selected ISDN channel 20. The initializer unit 14 broadcasts a DHCP discover message on LAN 22 to detect whether a Dynamic Host Configuration Protocol (DHCP) server 28 is present on the LAN 22. While it is essential to check for the existence of a server 28 at start-up, it is also preferred to check for the existence of such a server 28 periodically.

25

20

If a response is received from the server 28, initializer 14 sends a disable signal to the modem's own DHCP server 16. The modem will be assigned a static address, either by direct communication through console 15, or by remote

10

15

20

25

communication at configuration station 24 using the modem monitor program 26.

If no network DHCP server 28 is present on the LAN 22, then no response is received to the DHCP discover message sent by initializer 14. The DHCP server 16 is then not disabled, and it will be able to operate as a DHCP server on network 22. The modem 10 is assigned a static address, either by direct communication through console 15, or by remote communication at configuration station 24 using the modem monitor program 26. When modem 10 functions as a DHCP server, DHCP server 16 will reply to DHCP discover packets broadcasted by clients 30 and 32 (and possibly station 24) to configure their IP addresses. In the preferred embodiment, when the clients 30,32 are using dynamic addresses and the only DHCP server is 16, all the clients are configured by the modem's DHCP component 16 using addresses in the factory defined range of addresses: 192.168.1.2,....192.168.1.50

In the preferred embodiment, a client station 24 includes a modem monitor 26 which allows the user to manually set the active/inactive state of the DHCP server, in the event that the network manager wants to disable the DHCP server 16, or at a later time re-enable the DHCP server 16. The modem monitor interface is HTML-based and provides a simple interface.

Server 16 also handles a reinitialization, for example as a result of being turned off and on, without disrupting any clients on the network. Server 16 pings all addresses within its range at power on. Any addresses which have responded to the ping are placed on a reserved list 17 of unknown status addresses. These unknown addresses could be DHCP clients or static addresses. New clients requesting dynamic addresses are assigned new addresses within the range of the modem and which are not on the reserved list or list of other addresses

10

already assigned to DHCP clients since power on. Existing clients request a new address periodically, based on their lease time, which can vary from minutes to months. When an existing client having one of the reserved addresses requests a new dynamic address, the address is removed from the list of unknown and reserved addresses. This frees up the otherwise reserved address. As will be appreciated, a DHCP server would normally copy all address and lease time data to fixed storage and recover from a shut down by retrieving the data from fixed storage. According to the invention, the DHCP mechanism integrated into the modem does not require fixed storage, due to the use of its start-up check for addresses in-use and subsequent free-up of those addresses belonging to DHCP clients upon renewal.

CLAIMS

- 1. A network modem device comprising an integrated mechanism for dynamically assigning network addresses on a network, the device being characterized in that it further comprises a controller circuit connected to said integrated mechanism and detecting a presence of a dynamic address assignment server on the network, wherein said integrated mechanism is disabled when said server is detected.
- 2. The device according to claim 1, wherein said device is a digital network modem.
- 3. The device according to claim 2, wherein said device is an ISDN modem.
- 4. The device according to one of claims 1 to 3, wherein said integrated mechanism provides a DHCP server function.
- 5. The device according to claim 4, wherein said controller circuit broadcasts a DHCP discover message on the network and listens to a response to detect said presence of said server.
- 6. The device according to one of claims 1 to 5, further comprising a start-up mechanism and a memory store of unknown used addresses, said start-up mechanism checking the availability of addresses on the network and placing used addresses in the memory store of unknown used addresses, said integrated mechanism for dynamically assigning network addresses on a network selecting new addresses not included in said store of unknown used addresses, and removing addresses from said store of unknown used addresses when a

client having one of said addresses in said store of unknown used addresses requests a dynamically assigned address.

7. A method of enabling/disabling a mechanism for dynamically assigning network addresses on a network, said mechanism being integrated into a network modern device, the method comprising:

detecting a presence of a dynamic address assignment server on the network, and


disabling said integrated mechanism when said server is detected.

- 8. The method according to claim 7, wherein said device is a digital network modem.
- 9. The method according to claim 8, wherein said device is an ISDN modem.
- 10. The method according to one of claims 7 to 9, wherein said integrated mechanism provides a DHCP server function.
- 11. The method according to claim 10, wherein said detecting comprises broadcasting from said device onto said network a DHCP discover message and listening to a response to detect said presence of said server.
- 12. The method according to one of claims 7 to 11, further comprising: checking the availability of addresses on the network after power on and loss of memory of previously dynamically assigned addresses;

storing the used addresses in a store of unknown used addresses;

selecting new addresses not stored in response to a request for a dynamically assigned address; and

removing an address from said store of unknown used addresses when a client having one of said addresses in said store of unknown used addresses requests a dynamically assigned address.



Total Arm

Inter. unal Application No PCT/CA 99/01014

A CLASSI IPC 7	FICATION OF SUBJECT MATTER H04L29/12 H04L12/46		
According to	international Patent Classification (IPC) or to both national classifica	tion and IPC	
	SEARCHED		
Minimum do IPC 7	cumentation searched (classification system followed by classification H04L H04M	n symbols)	
Documentat	don searched other than minimum documentation to the extent that sa	ach documents are included in the fields se	arched
Electronic d	ata base consulted during the International search (name of data bas	e and, where practical, search terms used	
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the rele	want passages	Relevant to claim No.
Υ	EP 0 843 440 A (CANON INFORMATION INC) 20 May 1998 (1998-05-20)	SYST	1-4,7-10
A	abstract		5,6,11, 12
	column 1, line 1 -column 3, line column 5, line 18 -column 8, line column 9, line 30 -column 12, lin	40	
	_	/	
X Furti	her documents are listed in the continuation of box C.	Patent family members are listed	In annex.
"A" docume consid "E" earlier of filing d" "L" docume which chation "O" docume other of the "P" docume	ent defining the general state of the art which is not lered to be of particular relevance document but published on or after the international late ent which may throw doubts on priority claim(s) or its cited to establish the publication date of another n or other special reason (as specified) ent referring to an oral disclosure, use, exhibition or means ent published prior to the international filing date but han the pdority date claimed	"T" later document published after the lints or priority date and not in conflict with cited to understand the principle or the invention." "X" document of particular relevance; the cannot be considered novel or cannot involve an inventive step when the do. "Y" document of particular relevance; the cannot be considered to trivolve an indocument is combined with one or moments, such combination being obvious in the art. "8" document member of the same patent	the application but every underlying the salmed invention be considered to comment is taken alone starmed invention wentive step when the vice other such docu-us to a person skilled
	actual completion of the International search March 2000	Date of mailing of the International sec	arch report
Name and r	mailing address of the ISA European Patent Office, P.B. 5818 Patentiaan 2 NI. – 2280 HV Rijewijk Tel. (+31–70) 340–2040, Tx. 31 651 epo ni.	Authorized officer Lievens . K	

1



tnte. onel Application No PCT/CA 99/01014

		PCT/CA 99	/01014	
(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT				
tegory *	Citation of document, with indication, where appropriate, of the relevant passages		Refevent to claim No.	
	WO 98 26548 A (WHISTLE COMMUNICATIONS CORP; COBBS ARCHIE L (US); LI JIM Y (US); O) 18 June 1998 (1998-06-18) abstract page 1, line 27 -page 4, line 32 page 6, line 12-15 page 7, line 17 -page 10, line 30 page 11, line 32 -page 12, line 11 page 15, line 17-23 page 17, line 18 -page 20, line 32 figure 6		1-4,7-10 5,6,11, 12	
			·	

1



Information on patent family members

inten and Application No PCT/CA 99/01014

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0843440 A	20-05-1998	US 6021429 A JP 10164095 A	01-02-2000 19-06-1998
WO 9826548 A	18-06-1998	US 6012088 A AU 3572697 A EP 0953248 A	04-01-2000 03-07-1998 03-11-1999

PAJENT COOPERATION TREATY

From the INT	ERNATIONAL BUREAU
То:	
Assistant (Commissioner for Patents
	tes Patent and Trademark
Office	
Box PCT	
	D 0 00004

	From the INTERNATIONAL BUREAU
PCT	То:
NOTIFICATION OF ELECTION (PCT Rule 61.2)	Assistant Commissioner for Patents United States Patent and Trademark Office Box PCT Washington, D.C.20231 ETATS-UNIS D'AMERIQUE
Date of mailing (day/month/year) 04 July 2000 (04.07.00)	in its capacity as elected Office
International application No.	Applicant's or agent's file reference
PCT/CA99/01014	13693-4pctJA
International filing date (day/month/year)	Priority date (day/month/year)
29 October 1999 (29.10.99)	30 October 1998 (30.10.98)
Applicant	
MOINEAU, Gilbert	
The designated Office is hereby notified of its election made In the demand filed with the International Preliminary	
29 May 2000 (2	9.05.00)

1.	The designated Office is hereby notified of its election made:
	X in the demand filed with the International Preliminary Examining Authority on:
	29 May 2000 (29.05.00)
	in a notice effecting later election filed with the International Bureau on:
i	
2.	The election X was
	was not
	made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).
	·
	·

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland

Authorized officer

Claudio Borton

Telephone No.: (41-22) 338.83.38



(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference 13693-4pctJA		of Transmittal of International Search Report 220) as well as, where applicable, item 5 below.
International application No.	International filing date (day/month/year)	(Earliest) Priority Date (day/month/year)
PCT/CA 99/01014	29/10/1999	30/10/1998
Applicant EICON TECHNOLOGY CORPORAT	ION et al.	
This international Search Report has been according to Article 18. A copy is being to	n prepared by this International Searching Autansmitted to the International Bureau.	thority and is transmitted to the applicant
This International Search Report consists It is also accompanied by	of a total of sheets. a copy of each prior art document cited in this	s report.
Basis of the report a. With regard to the language, the language in which it was filed, unit	international search was carried out on the ba less otherwise indicated under this item.	ists of the International application in the
the international search w Authority (Rule 23.1(b)).	as carried out on the basis of a translation of	the International application furnished to this
was carried out on the basis of the		nternational application, the international search
=	mational application in computer readable for	m
	•	111.
	this Authority in written form.	
the statement that the sut	o this Authority in computer readble form. prequently furnished written sequence listing of	does not go beyond the disclosure in the
	s flied has been furnished. ormation recorded in computer readable form	is identical to the written sequence listing has been
2. Certain claims were four	nd unsearchable (See Box I).	
3. Unity of invention is lac	king (see Box II).	
4. With regard to the title,		
X the text is approved as su	bmitted by the applicant.	
the text has been establis	hed by this Authority to read as follows:	•
5. With regard to the abstract,		
The text is approved as su	hmitted by the annilcent	
the text has been establis		tty as it appears in Box III. The applicant may, port, submit comments to this Authority.
6. The figure of the drawings to be publ	shed with the abstract is Figure No.	1
X as suggested by the appli	cant.	None of the figures.
because the applicant fall	ed to suggest a figure.	
because this figure better	characterizes the invention.	·



International Application No PCT 99/01014

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 H04L29/12 H04L12/46

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols) IPC 7 - H04L - H04M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

	ENTS CONSIDERED TO BE RELEVANT	
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 843 440 A (CANON INFORMATION SYST INC) 20 May 1998 (1998-05-20)	1-4,7-10
A	abstract	5,6,11, 12
	column 1, line 1 -column 3, line 3 column 5, line 18 -column 8, line 40	
	column 9, line 30 -column 12, line 23	
	-/	

Further documents are listed in the continuation of box C.	Patent family members are listed in annex.				
Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or of the establish the publication date of another citation or of the repectal reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "&" document member of the same patent family				
Date of the actual completion of the International search 10 March 2000	Date of mailing of the International search report 23/03/2000				
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentiaan 2 NL – 2280 HV Rijswijk Tel. (+31–70) 340–2040, Tx. 31 651 epo ni, Facc (+31–70) 340–3018	Authorized officer Lievens, K				

1



Continue	ntion) DOCUMENTS CONSIDERED TO BE RELEVANT	
egory °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
	WO 98 26548 A (WHISTLE COMMUNICATIONS CORP; COBBS ARCHIE L (US); LI JIM Y (US); O) 18 June 1998 (1998-06-18) abstract	 1-4,7-10
	page 1, line 27 -page 4, line 32 page 6, line 12-15 page 7, line 17 -page 10, line 30 page 11, line 32 -page 12, line 11 page 15, line 17-23 page 17, line 18 -page 20, line 32 figure 6	12
-		

Information patent family members

PC1 99/01014

Patent document cited in search report	t	Publication date		Patent family member(s)		Publication date
EP 0843440	A	20-05-1998	US JP	6021429 10164095	A A	01-02-2000 19-06-1998
WO 9826548	A	18-06-1998	US AU EP	3572697	A A A	04-01-2000 03-07-1998 03-11-1999

10

15

PEPLACEDEN WO 00/27094 such networks. While computer networks were very uncommon a few years ago for home users, it is now economically feasible and desirable to interconnect computer devices in a home environment. Any simplification of the task of network management is important from the perspective of both increased reliability and reduced training for the network manager. DHCP therefore offers many practical advantages in managing a network, even for relatively small networks found in homes or small and medium businesses. While some network administrators have taken the time to obtain and install DHCP, many others have not, particularly in home and small business environments.

> While it would be advantageous to provide a DHCP server function integrated with a component to be added to a network, such as a digital network modem, for those who would benefit from a DHCP, it is imperative to avoid installing two DHCP servers on the same network, since the result would be confusion and malfunction. Furthermore, having to choose between one modem including DHCP functionality and another modem without DHCP requires the manufacture, distribution and stocking of separate types of modems, and complicates the purchasing choice.

20

25

Summary of the Invention

It is therefore an object of the invention to provide in a digital network modem (i.e. a router or gateway device) a mechanism for dynamically assigning network addresses on a LAN, such as DHCP, which mechanism has an autosense feature to automatically shut itself off when the modem detects that a similar device is present on the LAN.

According to the invention, there is provided a network modem device comprising an integrated mechanism for dynamically assigning network WO 00/27094 PCT/CA99/01014

- 3 -

addresses on a network. The device further comprises a controller circuit connected to the integrated dynamic network address assignment mechanism and detecting the presence of a dynamic address assignment server on the network. The integrated mechanism is disabled when the dynamic address assignment server on the network is detected.

The invention also provides a method of enabling/disabling a mechanism for dynamically assigning network addresses on a network, the mechanism being integrated into a network modem device. The method comprises detecting a presence of a dynamic address assignment server on the network, and disabling the integrated mechanism when the dynamic address assignment server is detected on the network.

It is yet another object of the invention to provide a mechanism for dynamically assigning network addresses on a LAN, such as DHCP, which is able to handle a reinitialization, for example as a result of being turned off and on, without disrupting any clients on the network. According to this feature, the mechanism for dynamically assigning network addresses pings all addresses within its range at power on. The mechanism then reserves any addresses which have responded. New clients requesting dynamic addresses are assigned new addresses within the range, and existing clients request a new addresse periodically. When an existing client having one of the reserved addresses requests a new dynamic address, the address is removed from the list of unkown and reserved addresses.

15

20

5

WO 00/27094 PCT/CA99/01014

- 7 -

CLAIMS

- 1. A network modem device comprising an integrated mechanism for dynamically assigning network addresses on a network, the device being characterized in that it further comprises a controller circuit connected to said integrated mechanism and detecting a presence of a dynamic address assignment server on the network, wherein said integrated mechanism is disabled when said server is detected.
- 2. The device according to claim 1, wherein said device is a digital network modern.
- 3. The device according to claim 2, wherein said device is an ISDN modem.
- 4. The device according to one of claims 1 to 3, wherein said integrated mechanism provides a DHCP server function.
- 5. The device according to claim 4, wherein said controller circuit broadcasts a DHCP discover message on the network and listens to a response to detect said presence of said server.
- 6. The device according to one of claims 1 to 5, further comprising a start-up mechanism and a memory store of unknown used addresses, said start-up mechanism checking the availability of addresses on the network and placing used addresses in the memory store of unknown used addresses, said integrated mechanism for dynamically assigning network addresses on a network selecting new addresses not included in said store of unknown used addresses, and removing addresses from said store of unknown used addresses when a

client having one of said addresses in said store of unknown used addresses requests a dynamically assigned address.

7. A method of enabling/disabling a mechanism for dynamically assigning network addresses on a network, said mechanism being integrated into a network modern device, the method comprising:

detecting a presence of a dynamic address assignment server on the network, and

disabling said integrated mechanism when said server is detected.

- 8. The method according to claim 7, wherein said device is a digital network modem.
- 9. The method according to claim 8, wherein said device is an ISDN modem.
- 10. The method according to one of claims 7 to 9, wherein said integrated mechanism provides a DHCP server function.
- 11. The method according to claim 10, wherein said detecting comprises broadcasting from said device onto said network a DHCP discover message and listening to a response to detect said presence of said server.
- 12. The method according to one of claims 7 to 11, further comprising: checking the availability of addresses on the network after power on and loss of memory of previously dynamically assigned addresses;

storing the used addresses in a store of unknown used addresses;

selecting new addresses not stored in response to a request for a dynamically assigned address; and

removing an address from said store of unknown used addresses when a client having one of said addresses in said store of unknown used addresses requests a dynamically assigned address.

PATENT COOPERATION TREATY





Fax 1 : 514-288-8389

From the

INTERNATIONAL PRELIMINARY EXAMINING AUTHORITY

To: SWABEY OGILVY RENAULT 1981 McGill College Avenue Suite 1600 Montréal, Québec H3A 2Y3 CANADA	SWASEY OLDER FOR ALGEBRA AND SERVICE STATE OF SERVICE STATE OF SERVICE	FOE O NOTIFICAL THE INTE	PCT ATION OF TRANSMITTAL STION ERNATIONAL PHELIMINARY (PCT Hule 71.1) 2 5. 01. 01
Applicant's or agent's file reference 13693-4pct		IP.	MPORTANT NOTIFICATION
International application No. PCT/CA99/01014	International filing date (da 29/10/1999	ay/month/year)	Priority date (day/month/year) 30/10/1998
Applicant	PATION et al		

- 1. The applicant is hereby notified that this International Preliminary Examining Authority transmits herewith the international preliminary examination report and its annexes, if any, established on the international application.
- 2. A copy of the report and its annexes, if any, is being transmitted to the International Bureau for communication to all the elected Offices.
- 3. Where required by any of the elected Offices, the International Bureau will prepare an English translation of the report (but not of any annexes) and will transmit such translation to those Offices.

4. REMINDER

The applicant must enter the national phase before each elected Office by performing certain acts (filing translations and paying national fees) within 30 months from the priority date (or later in some Offices) (Article 39(1)) (see also the reminder sent by the International Bureau with Form PCT/IB/301).

Where a translation of the international application must be furnished to an elected Office, that translation must contain a translation of any annexes to the international preliminary examination report. It is the applicant's responsibility to prepare and furnish such translation directly to each elected Office concerned.

For further details on the applicable time limits and requirements of the elected Offices, see Volume II of the PCT Applicant's Guide.

Name and mailing address of the IPEA/

Authorized officer

 European Patent Office D-80298 Munich

Tel. +49 89 2399 - 0 Tx: 523656 epmu d

Fax: +49 89 2399 - 4465

Ahrens, R

Tel.+49 89 2399-8136





PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Annlicant's	or age	ent's file reference	T		
13693-4pct			FOR FURTHER ACTION	See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)	
International application No.			International filing date (day/month	r/year) Priority date (day/month/year)	
PCT/CA99/01014			29/10/1999	30/10/1998	
International Patent Classification (IPC) or national classification and IPC H04L29/12					
Applicant EICON T	ECH	NOLOGY CORPORA	TION et al.		
	 This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36. 				
2. This f	REPO	RT consists of a total of	5 sheets, including this cover s	heet.	
b	This report is also accompanied by ANNEXES, i.e. sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).				
These	e ann	exes consist of a total of	4 sheets.		
This report contains indications relating to the following items:					
	⊠	Basis of the report			
	_	Priority '			
1111		•	pinion with regard to novelty, in	ventive step and industrial applicability	
iv	_	Lack of unity of invention	•		
V	<u> </u>				
VI VI		Certain documents cite			
VII	☒	Certain defects in the in	nternational application		
VIII					
Date of submission of the demand			Date of	completion of this report	
29/05/20	29/05/2000			2 5. 01. 01	
	Name and mailing address of the international			zed officer	
preliminary	Euro D-80	ining authority: ppean Patent Office 0298 Munich	Ferrar	i, J	
Tel. +49 89 2399 - 0 Tx: 523656 ep Fax: +49 89 2399 - 4465			· · · · · · · · · · · · · · · · · · ·	one No. +49 89 2399 8803	

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No. PCT/CA99/01014

I. Basis	of th	ne rej	port
----------	-------	--------	------

1.	resp the	This report has been drawn on the basis of (substitute sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to the report since they do not contain amendments (Rules 70.16 and 70.17).): Description, pages:						
	1,4-	6	as originally filed					
	2,3		as received on	05/01/2001	with letter of	04/01/2001		
	Clai	ms, No.:	·					
	1-10)	as received on	05/01/2001	with letter of	04/01/2001		
	Drawings, sheets:							
	1/1		as originally filed					
2. With regard to the language, all the elements marked above were available or furnished to this language in which the international application was filed, unless otherwise indicated under this in These elements were available or furnished to this Authority in the following language: , which				nder this item.	the			
	—							
		55.2 and/or 55.3)		the purposes of litter	national prelimina	y examination (under	· (u)	
3.	With regard to any nucleotide and/or amino acid sequence disclosed in the international application, the international preliminary examination was carried out on the basis of the sequence listing:							
		contained in the in	nternational application in	written form.			•	
		filed together with	n the international applica	tion in computer read	dable form.			
		furnished subseq	uently to this Authority in	written form.				
		furnished subseq	uently to this Authority in	computer readable f	orm.			
			at the subsequently furnis application as filed has be		ce listing does not	go beyond the disclos	ure in	
		The statement the listing has been for	at the information recorde urnished.	ed in computer reada	ble form is identica	al to the written seque	псе	
4.	The	amendments hav	re resulted in the cancella	tion of:				

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No. PCT/CA99/01014

		the description,	page.		
		•	pages:		. •
		the claims,	Nos.:		
		the drawings,	sheets:		
5.	☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)):				
		(Any replacement sh report.)	eet contair	ning such	amendments must be referred to under item 1 and annexed to this
6.	Add	itional observations, it	f necessar	y:	
٧.		soned statement un tions and explanatio			ith regard to novelty, inventive step or industrial applicability;
1.	Stat	ement			
	Nov	relty (N)	Yes: No:	Claims Claims	1-10
	Inve	entive step (IS)	Yes: No:	Claims Claims	1-10
	Indu	ustrial applicability (IA)	Yes: No:	Claims Claims	1-10
2.		itions and explanation	s		

VII. Certain defects in the international application

The following defects in the form or contents of the international application have been noted: see separate sheet

International application No. PCT/CA99/01014

EXAMINATION REPORT - SEPARATE SHEET

Ad section V.:

CLAIMS 1, 6

The present application relates to a network modem device and to a method for dynamically assigning network addresses on a LAN.

Prior art document EP-A-0 843 440 discloses a method which controls a network device on a local area network to operate as a list manager which maintains a list of device addresses (dynamic addresses) for the LAN. The method determines whether a list manager is operating on the LAN, and in case of detecting such a list manager, controlling the network device to operate only as a slave on the LAN, and when no list manager is detected on the LAN, controlling the network device to operate as the list manager for the LAN.

In order to prevent confusion with an existing dynamic host configuration protocol (DHCP) server on the LAN, the solution proposed by the present application and in particular by the apparatus and method according to claims 1 and 6 respectively, provides an autosense mechanism to detect the existence of a DHCP server on the LAN and to disable the internal, built-in DHCP mechanism when said server is detected. At power-on, the network modem device checks the availability of addresses in use on the network prior to operation. Addresses in use are placed in a list in a store of unknown addresses, and are not assigned to clients requesting DHCP addresses. When a DHCP client requests an address and has as its current address one of the addresses on said list, the current address is removed from the list.

This specific concept as defined by the combination of features of claim 1 or 6 respectively, is not to be taken or obviously derived from one of the documents cited in the International Search Report in the sense of Rule 33(1) PCT.

The requirements of Article 33 PCT are therefore fulfilled for these independent claims.

INTERNATIONAL PRELIMINARY **EXAMINATION REPORT - SEPARATE SHEET**

International application No. PCT/CA99/01014

CLAIMS 2-5, 7-10

Dependent claims 2 to 5 and 7 to 10 contain further details of the network modem device of claim 1 and the enabling/disabling method of claim 6 respectively. As they are dependent on these claims, they also satisfy the requirements of Article 33 PCT.

Ad section VII.:

The following deficiencies are found in the application:

- a) The claims do not meet the requirements of Rule 6.2b PCT in that they do not contain reference signs.
- b) Independent claims 1 and 6 do not meet the requirements of Rule 6.3b PCT in that they are not divided in the correct two-part form.

-2-

such networks. While computer networks were very uncommon a few years ago for home users, it is now economically feasible and desirable to interconnect computer devices in a home environment. Any simplification of the task of network management is important from the perspective of both increased reliability and reduced training for the network manager. DHCP therefore offers many practical advantages in managing a network, even for relatively small networks found in homes or small and medium businesses. While some network administrators have taken the time to obtain and install DHCP, many others have not, particularly in home and small business environments.

10

15

30

5

While it would be advantageous to provide a DHCP server function integrated with a component to be added to a network, such as a digital network modem, for those who would benefit from a DHCP, it is imperative to avoid installing two DHCP servers on the same network, since the result would be confusion and malfunction. Furthermore, having to choose between one modem including DHCP functionality and another modem without DHCP requires the manufacture, distribution and stocking of separate types of modems, and complicates the purchasing choice.

European Patent Application No. 0 843 440 to Danknick, Dan and entitled "Network Device Which Maintains A List Of Device Addresses" describes a method which controls a network device on a local area network to operate as a list manager which maintains a list of device addresses for the LAN. It detects if a list manager is operating on the LAN and if so, controls the device to operate as a slave. If not, the device becomes the list manager on the LAN for the various devices on the LAN.

Summary of the Invention

It is therefore an object of the invention to provide in a digital network modem (i.e. a router or gateway device) a mechanism for dynamically assigning network addresses on a LAN, such as DHCP, which mechanism has an auto-sense feature to automatically shut itself off when the modern detects that a similar device is present on the LAN.

According to the invention, there is provided a network modern device comprising an integrated mechanism for dynamically assigning network addresses on a network, the network modern device being characterized in that it

10

15

20

25

30

comprises: a controller circuit detecting a presence of a dynamic address assignment server on the network; an interrupter disabling the integrated mechanism when the controller circuit detects the server; and a memory store of unknown used addresses; wherein the integrated mechanism comprises: a start-up mechanism checking the availability of addresses on the network and placing used addresses in the memory store of unknown used addresses; an address manager selecting new addresses not included in the store of unknown used addresses, and removing addresses from the store of unknown used addresses when a client having one of the addresses in the store of unknown used addresses requests a dynamically assigned address.

The invention also provides a method of enabling/disabling a mechanism for dynamically assigning network addresses on a network, the mechanism being integrated into a network modem device, the method comprising: detecting a presence of a dynamic address assignment server on the network; and disabling the integrated mechanism when the server is detected; checking the availability of addresses on the network after power on and loss of memory of previously dynamically assigned addresses; storing the used addresses in a store of unknown used addresses; selecting new addresses not stored in response to a request for a dynamically assigned address; and removing an address from the store of unknown used addresses when a client having one of the addresses in the store of unknown used addresses requests a dynamically assigned address.

It is yet another object of the invention to provide a mechanism for dynamically assigning network addresses on a LAN, such as DHCP, which is able to handle a re-initialization, for example as a result of being turned off and on, without disrupting any clients on the network. According to this feature, the mechanism for dynamically assigning network addresses pings all addresses within its range at power on. The mechanism then reserves any addresses which have responded. New clients requesting dynamic addresses are assigned new addresses within the range, and existing clients request a new address periodically. When an existing client having one of the reserved addresses requests a new dynamic address, the address is removed from the list of unknown and reserved addresses.

25

-7-

CLAIMS

- 1. A network modern device comprising an integrated mechanism for dynamically assigning network addresses on a network, the network modern device being characterized in that it comprises:
- a controller circuit detecting a presence of a dynamic address assignment server on the network;
- an interrupter disabling said integrated mechanism when said controller circuit detects said server; and
- a memory store of unknown used addresses; wherein said integrated mechanism comprises
 - a start-up mechanism checking the availability of addresses on the network and placing used addresses in said memory store of unknown used addresses;
- an address manager selecting new addresses not included in said store of unknown used addresses, and removing addresses from said store of unknown used addresses when a client having one of said addresses in said store of unknown used addresses requests a dynamically assigned address.
- 20 2. The device according to claim 1, wherein said network modem device is a digital network modem.
 - 3. The device according to claim 2, wherein said network modem device is an ISDN modem.
 - 4. The device according to one of claims 1 to 3, wherein said integrated mechanism provides a DHCP server function.

AMENDED SHEET

: : :

ona. 4. čoji Tijaverm

15

30

- 5. The device according to claim 4, wherein said controller circuit broadcasts a DHCP discover message on the network and listens to a response to detect said presence of said server.
- 5 6. A method of enabling/disabling a mechanism for dynamically assigning network addresses on a network, said mechanism being integrated into a network modem device, the method comprising:

detecting a presence of a dynamic address assignment server on the network; and

disabling said integrated mechanism when said server is detected;

checking the availability of addresses on the network after power on and
loss of memory of previously dynamically assigned addresses;

storing the used addresses in a store of unknown used addresses;

selecting new addresses not stored in response to a request for a dynamically assigned address; and

removing an address from said store of unknown used addresses when a client having one of said addresses in said store of unknown used addresses requests a dynamically assigned address.

- 7. The method according to claim 6, wherein said device is a digital network modem.
 - 8. The method according to claim 7, wherein said device is an ISDN modem.
- 25 9. The method according to one of claims 6 to 8, wherein said integrated mechanism provides a DHCP server function.
 - 10. The method according to claim 9, wherein said detecting comprises broadcasting from said device onto said network a DHCP discover message and listening to a response to detect said presence of said server.